



Fiber Optic Cable, 24-fiber, OM4, 2000 m, aqua

Product Classification

Regional Availability

Asia | Australia/New Zealand | EMEA

Portfolio

CommScope®

Product Type

Fiber indoor/outdoor cable

General Specifications

Cable Type

Loose tube

Jacket Color

Aqua

Subunit Type

Gel-filled

Total Fiber Count

24

Dimensions

Cable Length

2000 m | 6,561.68 ft

Diameter Over Jacket

8 mm | 0.315 in

Mechanical Specifications

Minimum Bend Radius, loaded

160 mm | 6.299 in

Minimum Bend Radius, unloaded

110 mm | 4.331 in

Tensile Load, long term, maximum

650 N | 146.126 lbf

Tensile Load, short term, maximum

1300 N | 292.252 lbf

Optical Specifications

Fiber Type

OM4

Optical Specifications, Wavelength Specific

Attenuation, maximum

1.00 dB/km @ 1,300 nm | 3.00 dB/km @ 850 nm

Standards Compliance

IEC 60794-1 | TIA-492AAAD (OM4)

2-1716001-2 | C-024-CN-5K-M24AQ/40G/GY/D

Environmental Specifications

Installation temperature	-5 °C to +50 °C (+23 °F to +122 °F)
Operating Temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Storage Temperature	-20 °C to +70 °C (-4 °F to +158 °F)
EN50575 CPR Cable EuroClass Fire Performance	Dca
EN50575 CPR Cable EuroClass Smoke Rating	s2
EN50575 CPR Cable EuroClass Droplets Rating	d2
EN50575 CPR Cable EuroClass Acidity Rating	a1
Environmental Space	Universal Low Smoke Zero Halogen (ULSZH)

Packaging and Weights

Cable weight	74 kg/km 49.726 lb/kft
---------------------	--------------------------

Included Products

CS-5K-LT	-	LazrSPEED® 550 OM4 Bend-Insensitive Multimode Fiber
----------	---	---

* Footnotes

Operating Temperature Specification applicable to non-terminated bulk fiber cable